


TACK COAT
(SEE SECTION 1.E.4)



SURFACE COURSE

1" S9.5B
FINAL LIFT TO BE APPLIED UPON MEETING ONE OF THE FOLLOWING CONDITIONS:
1) 75% DEVELOPMENT OCCUPANCY,
2) 1 YEAR FROM INTERMEDIATE COURSE PLACEMENT,
3) FOR ETJ STREETS, FINAL 1" MAY BE PLACED WHEN APPROVED BY NCDOT.

INTERMEDIATE COURSE

1-1/2" S9.5C OR S9.5B

BASE COURSE

8" COMPACTED AGGREGATE BASE COURSE, OR 4" BCBC TYPE B25.0C
SHOULD ENTIRE DEVELOPMENT HAVE A CBR OF 6 OR GREATER, THEN AN ALTERNATIVE BASE COURSE PAVEMENT DESIGN MAY BE SUBMITTED TO THE CITY FOR APPROVAL.

SUBGRADE

COMPACTED SUBGRADE (SEE CLDS SPECIFICATIONS AND SPECIAL PROVISIONS SECTION 1.A.18)

TYPICAL PAVEMENT SECTION

NOTES:

1. SIDEWALK SHALL BE ON BOTH SIDES OF STREET AND LOCATED ON LOT SIDE OF DITCH.
2. SIDEWALK OR SHARED-USE PATH (SUP) LOCATED OUTSIDE OF STREET RIGHT OF WAY SHALL BE LOCATED IN A PERMANENT SIDEWALK AND UTILITY EASEMENT (SUE) EXTENDING 2' BEHIND BACK OF SIDEWALK OR SUP.
3. APPROVAL BY THE CITY IS REQUIRED PRIOR TO USING DITCH TYPE SECTION.

KEY

Ⓢ = 4" CONCRETE SIDEWALK

NOT TO SCALE



CITY OF CHARLOTTE
LAND DEVELOPMENT STANDARDS
INCLUDES CHARLOTTE ETJ

LOCAL RESIDENTIAL
TYPICAL DITCH TYPE STREET SECTION

STD. NO.	REV.
11.02	23