



NOTES:

1. CONCRETE PAVERS PERMITTED UNDER AN ENCROACHMENT AGREEMENT WITH ALL APPLICABLE AGENCIES (CDOT OR NCDOT)
2. 4 1/2" x 9" x 60mm FOR SIDEWALKS
3. 4 1/2" x 9" x 80mm FOR DRIVEWAYS
4. BATCH DESIGN SHALL CONSIST OF 450 lbs. CEMENT / 2,085 lbs. AGGREGATES / MINIMUM 12 lbs. OF INORGANIC COLOR PIGMENT
5. COLOR SHALL BE A THREE-COLOR BLEND OF 15% BRICK RED, 35% MIDNIGHT BLACK, AND 50% BAJA RED TO CREATE A DARK ROSE, MOTTLED PAVEMENT SURFACE
6. PAVERS SHALL HAVE A UNIFORM SURFACE TEXTURE THAT IS NOT UNUSUALLY COARSE OR PITTED
7. SHALL BE INSTALLED ON A CONCRETE SUBSLAB BASE (50.01B)
8. PAVER JOINTS SHALL BE TIGHT AND FILLED WITH MANUFACTURED SAND FINES
9. VERTICAL SURFACE DISCONTINUITIES SHOULD BE MINIMIZED AND SHALL NOT EXCEED 1/4"

NOT TO SCALE



CITY OF CHARLOTTE
LAND DEVELOPMENT STANDARDS
 INCLUDES CHARLOTTE ETJ

PRECAST CONCRETE PAVERS
FOR UPTOWN STREETScape

STD. NO.	REV.
50.01A	23