



**PLAN VIEW**

**SECTION A-A**

**NOTES:**

1. BRUSH SHALL BE A VARIETY OF DIAMETERS AND SHALL BE LAID GENERALLY PERPENDICULAR TO FLOW AND COMPACTED BY DIRT.
2. LAYERS SHALL BE 65% BRUSH OF A VARIETY OF SIZES WITH 25% ON SITE MATERIAL FILLING VOIDS AND 10% 2"-10" RIP RAP.
3. BRUSH SHOULD BE BROUGHT UP IN 6"-8" LIFTS.
4. GRADING ABOVE THE TOE WOOD IS PER THE TYPICAL SECTION AND/OR GRADING PLAN.

**DESIGN VARIABLES**

	EXAMPLE	REACH _	REACH _
HEIGHT OF TOE WOOD	2.5'	--	--
WIDTH OF TOE WOOD	7'	--	--

\*ENGINEER TO ADJUST AS NECESSARY, MINIMUMS CANNOT BE ADJUSTED WITHOUT CITY APPROVAL

NOT TO SCALE



**CHARLOTTE-MECKLENBURG**  
**STORM WATER SERVICES**  
 GENERIC DETAIL REQUIREMENTS

**TOE WOOD**

DRAFT - NOT TO BE USED FOR CONSTRUCTION

SHEET NUMBER	
1 OF 1	
STD. NO.	REV.
XX.XX	